



The Next Level of HD - H.265 2/4/5 Megapixel Cameras

Unifore H.265/HEVC Super HD Series

Megapixel Cameras with Excellent Image Quality



Features

- Leveraging Hisilicon H.265 SoC
- Starvis, HDR megapixel CMOS sensors
- Up to 5-megapixel image resolution
- H.265/H.264/MJPEG codec
- Motorized 2.8-12mm/3.6-10mm lens
- D-WDR, True-WDR, BLC/HLC
- Smart ROI video encoding
- Smart intelligent video analysis
- Built-in IR illuminators, effective up to 50 meters
- IP67, IK10, whole aluminum case
- Audio I/O, Alarm I/O, USB, RS485
- ONVIF 2.4 (Profile S), RTSP compliant

Unifore Proven H.265 Surveillance Solution

Unifore offers you H.265/HEVC HD network video recorders that are fully compatible with Unifore H.265 Super HD series cameras. The H.265 NVRs can allow you setup a highly integrated and reliable video surveillance solution that reducing the integration effort and maintenance costs for project installers.

4K
ULTRA HD

4K UHD H.265
NETWORK VIDEO RECORDER



3rd Party NVR Compatible:

HIKVISION

DAHUA

AXIS
COMMUNICATIONS

SONY

Panasonic

SANYO

BOSCH

SAMSUNG

Honeywell

Ambarella

VIVOTEK
台灣 晶 睿


uniview

MEGAPIXEL IP CAMERAS

H.265 SUPER HD SERIES IP CAMERAS

5MP/4MP/FULL HD RESOLUTION

Unifore Super HD series cameras employ the professional HDR CMOS image sensor from Panasonic, OmniVision, Sony. They enable the camera to capture up to 5-megapixel resolution video with exceptional image quality.




SAVE 50% BANDWIDTH STORAGE

Utilizing the next generation H.265/HEVC video compression to reduce both bandwidth and storage consumption by up to 50% while retaining the highest standard in image quality.




P2P, POE, EDGE STORAGE

The built-in PoE feature provides much easier connection and installation with cost saving on network environment also efficient maintenance, extra P2P, SD card storage.



HDR/WDR CMOS SENSOR

Unifore adopts megapixel HDR/WDR CMOS image sensor to produce high quality megapixel HDR video under extreme variations of bright and dark conditions, ensuring high contrast and excellent scene reproduction.



MOTORIZED ZOOM LENS

Super HD series IP cameras can be equipped with the motorized zoom lens, supporting auto-focus, manual remote zoom&focus, and 4x optical zoom function.



Without 4x Optical Zoom

With 4x Optical Zoom

FREE VMS AND MOBILE APP

We are providing free video management software, which supporting central video monitoring and recording, as well as e-map, log, alarm control, motion detection, PTZ, remotely mobile surveillance.



UNIFORE

SECURE YOUR HOME & BUSINESS






CCTV & Intergrated Surveillance Solution



NS4025V5-D
NS2025V5-A
NS4025V5-A
NS5025V5-A

Model	NS4025V5-D	NS2025V5-A	NS4025V5-A	NS5025V5-A
Feature	HDR	WDR	HDR	Starvis
CMOS type	OmniVision	Panasonic	OmniVision	Sony
CMOS model	1/3" OV4689	1/3" MN34229	1/3" OV4689	1/1.8" IMX178
Image output	4MP:2592x1520 3MP:2048x1050 1080P:1920x1080	1080P:1920x1080 720P: 1280x720	4MP:2592x1520 3MP:2048x1050 1080P:1920x1080	5MP: 2592x1944 1080P:1920x1080
Min. Illumination	0.01Lux/0Lux	0.01Lux/0Lux	0.01Lux/0Lux	0.001Lux/0Lux
Lens	2.8-12mm manual/motorized zoom lens			3.6-10mm
Shutter Speed	1/60Sec 1/100,000Sec, Shutter Speed Adjustable			
AGC & WB	AGC: Auto, high, media, low; White Balance: Auto, Close			
S/N ratio	>50dB			
Gamma correction	>0.45			
Sync. system	internal			
Infrared	3pcs Infrared Array Illuminators			
IR Range	50 meters			
Network Steadiness	Auto Reconnect, Register, UPNP, HB Display, Synchronization			
Protocols	Onvif2.4,PPPOE,DHCP,TCP/IP,HTTP,UDP,RTP/RTCP, RTSP,UPNP,SMTP,FTP,NTP,DDNS,DNS			
Dual Stream	Dual Stream Transfer(H.264 CBR/VBR Adjustable) Main Stream: 1M-8Mbps, With Local Skim, SD Card etc. Sub-Stream: 0.5Kbps-2Mbps, With Network Transfer, 3G Access.			
Upgrade	Support Remote Upgrade, With Password Protect.			
Wireless	N/A			
Optional features	802.3af PoE (Optional)			
Zoom function	Image Frame Selection Amplification Function, Convenient to Capture the Enlarged Picture Details			
Smart alarm	Motion detect, Video Shelter, I/O Alarm for Video Lost, IP Address Conflict, Store Abnormal.			
Weatherproof	IP67 rated weatherproof design			
3-Axis Adjustment	3-Axis bracket for ceiling/wall mountable installation			
Effective pixel	2592*1520	1920*1080	2592*1520	2592*1944
Frame speed	4MP@15FPS	2MP@25/30FPS	4MP@25/30FPS	5MP@25/30FPS
Image capture	JPEG for Local Storage			
Image setting	Saturation, Luminance, Contrast, Hue, Brightness, Gama			
Image rotation	Mirror, Flip, 90/70 Degree Rotation			
Audio Encoding	G.726/G.722/G.711 Standard			
Audio Function	2-way Audio Intercom			
Power Supply	DC Female Connector, 12V DC			
Network Interface	1CH 10M/100M Ethernet RJ45			
Alarm	N/A	1CH Alarm I/O	1CH Alarm I/O	1CH Alarm I/O
Working Enviroment	Temperature-10- +60, Humidity<90%			
Power Consumption	DC 12V±5% , Max: 6W			



UNIFORE

SECURE YOUR HOME & BUSINESS



CCTV & Intergrated Surveillance Solution



NS4025V58-D
NS2025V58-A
NS4025V58-A
NS5025V58-A

Model	NS4025V58-D	NS2025V58-A	NS4025V58-A	NS5025V58-A
Feature	HDR	WDR	HDR	Starvis
CMOS type	OmniVision	Panasonic	OmniVision	Sony
CMOS model	1/3" OV4689	1/3" MN34229	1/3" OV4689	1/1.8" IMX178
Image output	4MP:2592x1520	1080P:1920x1080	4MP:2592x1520	5MP: 2592x1944
	3MP:2048x1050	720P: 1280x720	3MP:2048x1050	1080P:1920x1080
	1080P:1920x1080		1080P:1920x1080	
Min. Illumination	0.01Lux/0Lux	0.01Lux/0Lux	0.01Lux/0Lux	0.001Lux/0Lux
Lens	2.8-12mm manual/motorized zoom lens			3.6-10mm
Shutter Speed	1/60Sec 1/100,000Sec, Shutter Speed Adjustable			
AGC & WB	AGC: Auto, high, media, low; White Balance: Auto, Close			
S/N ratio	>50dB			
Gamma correction	>0.45			
Sync. system	internal			
Infrared	3pcs Infrared Array Illuminators			
IR Range	50 meters			
Network Steadiness	Auto Reconnect, Register, UPNP, HB Display, Synchronization			
Protocols	Onvif2.4,PPPOE,DHCP,TCP/IP,HTTP,UDP,RTP/RTCP, RTSP,UPNP,SMTP,FTP,NTP,DDNS,DNS			
Dual Stream	Dual Stream Transfer(H.264 CBR/VBR Adjustable)			
	Main Stream: 1M-8Mbps, With Local Skim, SD Card etc. Sub-Stream: 0.5Kbps-2Mbps, With Network Transfer, 3G Access.			
Upgrade	Support Remote Upgrade, With Password Protect.			
Wireless	N/A			
Optional features	802.3af PoE (Optional)			
Zoom function	Image Frame Selection Amplification Function, Convenient to Capture the Enlarged Picture Details			
Smart alarm	Motion detect, Video Shelter, I/O Alarm for Video Lost, IP Address Conflict, Store Abnormal.			
Weatherproof	IP67 rated weatherproof design			
3-Axis Adjustment	3-Axis bracket for ceiling/wall mountable installation			
Effective pixel	2592*1520	1920*1080	2592*1520	2592*1944
Frame speed	4MP@15FPS	2MP@25/30FPS	4MP@25/30FPS	5MP@25/30FPS
Image capture	JPEG for Local Storage			
Image setting	Saturation, Luminance, Contrast, Hue, Brightness, Gama			
Image rotation	Mirror, Flip, 90/70 Degree Rotation			
Audio Encoding	G.726/G.722/G.711 Standard			
Audio Function	2-way Audio Intercom			
Power Supply	DC Female Connector, 12V DC			
Network Interface	1CH 10M/100M Ethernet RJ45			
Alarm	N/A	1CH Alarm I/O	1CH Alarm I/O	1CH Alarm I/O
Working Enviroment	Temperature-10- +60, Humidity<90%			
Power Consumption	DC 12V±5% , Max: 6W			





NK4025D1-D



Model	NS4025D1-D
Feature	HDR
CMOS type	OmniVision
CMOS model	1/3" OV4689
Image output	4MP:2592x1520 3MP:2048x1050 1080P:1920x1080
Min. Illumination	0.01Lux/0Lux
Lens	2.8-12mm manual vari-focal lens
Shutter Speed	1/60Sec 1/100,000Sec, Shutter Speed Adjustable
AGC & WB	AGC: Auto, high, media, low; White Balance: Auto, Close
S/N ratio	>50dB
Gamma correction	>0.45
Sync. system	internal
Infrared	35pcs F5 Infrared Illuminators
IR Range	30 meters
Network Steadiness	Auto Reconnect, Register, UPNP, HB Display, Synchronization
Protocols	Onvif 2.4, PPPOE, DHCP, TCP/IP, HTTP, UDP, RTP/RTCP, RTSP, UPNP, SMTP, FTP, NTP, DDNS, DNS
Dual Stream	Dual Stream Transfer(H.264 CBR/VBR Adjustable) Main Stream: 1M-8Mbps, With Local Skim, SD Card etc. Sub-Stream: 0.5Kbps-2Mbps, With Network Transfer, 3G Access.
Upgrade	Support Remote Upgrade, With Password Protect.
Wireless	N/A
Optional features	802.3af PoE (Optional)
Zoom function	Image Frame Selection Amplification Function, Convenient to Capture the Enlarged Picture Details
Smart alarm	Motion detect, Video Shelter, I/O Alarm for Video Lost, IP Address Conflict, Store Abnormal.
Weatherproof	IP67 rated weatherproof design
3-Axis Adjustment	3-Axis bracket for ceiling/wall mountable installation
Effective pixel	2592*1520
Frame speed	4MP@15FPS; 3MP@25/30FPS
Image capture	JPEG for Local Storage
Image setting	Saturation, Luminance, Contrast, Hue, Brightness, Gama
Image rotation	Mirror, Flip, 90/70 Degree Rotation
Audio Encoding	G.726/G.722/G.711 Standard
Audio Function	2-way Audio Intercom
Power Supply	DC Female Connector, 12V DC
Network Interface	1CH 10M/100M Ethernet RJ45
Alarm	N/A
Working Enviroment	Temperature-10-+60, Humidity<90%
Power Consumption	DC 12V±5% , Max: 6W

UNIFORE

SECURE YOUR HOME & BUSINESS



CCTV & Intergrated Surveillance Solution



NK2025V15-A
NK4025V15-A
NK5025V15-A

Model	NK2025V15-A	NK4025V15-A	NK5025V15-A
Feature	WDR	HDR	Starvis
CMOS type	Panasonic	OmniVision	Sony
CMOS model	1/3" MN34229	1/3" OV4689	1/1.8" IMX178
Image output	1080P:1920x1080	4MP:2592x1520	5MP: 2592x1944
	720P: 1280x720	3MP:2048x1050	1080P:1920x1080
Min. Illumination	0.01Lux/0Lux	0.01Lux/0Lux	0.001Lux/0Lux
Lens	2.8-12mm manual/motorized zoom lens		3.6-10mm manual/motorized
Shutter Speed	1/60Sec 1/100,000Sec, Shutter Speed Adjustable		
AGC & WB	AGC: Auto, high, media, low; White Balance: Auto, Close		
S/N ratio	>50dB		
Gamma correction	>0.45		
Sync. system	internal		
Infrared	30pcs F5 Blue Infrared Illuminators		
IR Range	30 meters		
Network Steadiness	Auto Reconnect, Register, UPNP, HB Display, Synchronization		
Protocols	Onvif2.4,PPPOE,DHCP,TCP/IP,HTTP,UDP,RTP/RTCP, RTSP,UPNP,SMTP,FTP,NTP,DDNS,DNS		
Dual Stream	Dual Stream Transfer(H.264 CBR/VBR Adjustable)		
	Main Stream: 1M-8Mbps, With Local Skim, SD Card etc. Sub-Stream: 0.5Kbps-2Mbps, With Network Transfer, 3G Access.		
Upgrade	Support Remote Upgrade, With Password Protect.		
Wireless	N/A		
Optional features	802.3af PoE (Optional)		
Zoom function	Image Frame Selection Amplification Function, Convenient to Capture the Enlarged Picture Details		
Smart alarm	Motion detect, Video Shelter, I/O Alarm for Video Lost, IP Address Conflict, Store Abnormal.		
Weatherproof	IP67 rated weatherproof design		
3-Axis Adjustment	3-Axis bracket for ceiling/wall mountable installation		
Effective pixel	1920*1080	2592*1520	2592*1944
Frame speed	2MP@25/30FPS	4MP@25/30fps	5MP@25/30FPS
Image capture	JPEG for Local Storage		
Image setting	Saturation, Luminance, Contrast, Hue, Brightness, Gama		
Image rotation	Mirror, Flip, 90/70 Degree Rotation		
Audio Encoding	G.726/G.722/G.711 Standard		
Audio Function	2-way Audio Intercom		
Power Supply	DC Female Connector, 12V DC		
Network Interface	1CH 10M/100M Ethernet RJ45		
Alarm	N/A	1CH Alarm I/O	1CH Alarm I/O
Working Enviroment	Temperature-10- +60, Humidity<90%		
Power Consumption	DC 12V±5% , Max: 6W		

